

## Installing Statit For ProHelp™ EPM

*This application note provides an overview for how to install Statit for ProHelp™ EPM. Questions, concerns, or comments should be sent to the Mattec Customer Service Department.*

The examples in this document assume that the ProHelp™ EPM software files are located in the `C:\Program Files\Mattec\ProHelp` directory.

### 1. Upgrading from a previous version of Statit / ProHelp™ EPM

Before upgrading to a new version of Statit (or ProHelp™ EPM), you should backup the Statit license files remove the existing Statit software. To do this, follow these steps:

- Backup the Statit license files in the directory `..\statit\License`. If you fail to perform this step, it will be necessary to contact Mattec to attempt to determine your existing license number.
- Remove Statit by running `unwise.exe` in the `..\statit` directory.
- Install Statit on the Server and Workstations as described in the following sections.

### 2. Installing Statit (Server)

To install Statit on the ProHelp™ EPM server, follow these steps:

- Load the ProHelp™ EPM software as required. Statit files are copied into the `C:\Program Files\Mattec\ProHelp\Statit` directory.
- Run `..\statit\setup.exe`. Select to install the Statit software in the same directory. Reply to the prompts as required.
- Edit the `..\statit\License` files and enter the license number supplied by MATTEC Corporation. If you are upgrading, simply copy your backup of the license files into this directory.

- Copy the file `..\Statit\statit.ini` into the `..\Statit\Config` directory. This file has been modified by MATTEC and will be used in place of the one supplied by StatWare.
- Copy the file `..\Statit\statit.stm` into the `..\Statit\Forms` directory. This file has been modified by MATTEC and will be used in place of the one supplied by StatWare.
- Edit the file `..\Statit\Mattec\mattec_system1.stc` and modify the `epm_dbname` (database name), `epm_server` (server name), `epm_sysno` (typically "1"), and `epm_path` (directory where `\tmp` folder is located) as required.
- Manually create the folder `C:\tmp`, where `C:\tmp` is defined by the `epm_path` variable in the `mattec_system1.stc` file.

Note that separate `..\Statit\Mattec\mattec_system?.stc` files (with differing `epm_sysno`) will exist for each system that is defined in the System Names file.

### 3. Installing Statit (Client)

After installing Statit and ProHelp™ EPM on the server, it is necessary to install Statit on each workstation that will utilize the Statit software. To do this, follow these steps:

- Using Network Neighborhood on the client workstation, navigate to the Statit directory on the server computer.
- Run `..\Statit\NSetup.exe`. Follow the prompts as required.
- Manually create the folder `C:\tmp`, where `C:\tmp` is defined by the `epm_path` variable in the `mattec_system1.stc` file on the server.